

OSHA-COMPLIANT EXIT SIGNS



Jalite Meets The Code

Use Jalite's OSHA compliant exit signs to fulfill the mandate outlined below in Section 1910.37. Our OSHA compliant signs have the exact 6" high letters with 3/4" stroke widths as mandated by code.

And More

Our signs exceed the code! Jalite AAA photoluminescent material provides safety in light **and** dark conditions, should a power outage occur.

OSHA Federal Register

Section 1910.37(b)(4) states:

"If the direction of travel to the exit or exit discharge is not immediately apparent, signs must be posted along the exit access indicating the direction of travel to the nearest exit and exit discharge. Additionally, the line-of-sight to an exit sign must clearly be visible at all times."

Section 1910.37(b)(7)

states: "Each exit sign must have the word "Exit" in plainly legible letters not less than six inches (15.2 cm) high, with the principal strokes of the letters in the word "Exit" not less than three-fourths of an inch (1.9 cm) wide."



Shown without self adhesive chevrons



Part Number: US443

Size: 13" x 7.75"
(330 x 195 mm)

Material: Jalite AAA Rigid PVC

- Reliably identify the direction to the nearest exit under both normal and emergency conditions.
- 6" Letter height and 3/4" letter stroke width as prescribed by OSHA
- Jalite AAA material for ultra-high initial and long lasting luminance
- Small unobtrusive profile engineered for 100-150 ft. viewing distances in normal light conditions
- Available with or without frame
- Both left and right peel-and-stick chevrons are provided to indicate direction of travel

